

# Switch-mode Power Rectifier

## MBR2535CTLG

### Features and Benefits

- Low Forward Voltage
- Low Power Loss/High Efficiency
- High Surge Capacity
- 150°C Operating Junction Temperature
- 25 A Total (12.5 A Per Diode Leg)
- This Device is Pb-Free and is RoHS Compliant\*

### Applications



- Power Supply – Output Rectification
- Power Management
- Instrumentation

### Mechanical Characteristics

- Case: Epoxy, Molded
- Epoxy Meets UL 94, V-0 @ 0.125 in
- Weight: 1.9 Grams (Approximately)
- Finish: All External Surfaces Corrosion Resistant and Terminal Leads are Readily Solderable
- Lead Temperatures for Soldering Purposes: 260°C Max. for 10 Seconds
- ESD Rating: Human Body Model 3B  
Machine Model C


\*For additional information on our Pb-Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

## SCHOTTKY BARRIER RECTIFIER 25 AMPERES, 35 VOLTS



TO-220  
CASE 221A  
STYLE 6

### MARKING DIAGRAM



A = Assembly Location  
Y = Year  
WW = Work Week  
B2535L = Device Code  
G = Pb-Free Package  
AKA = Polarity Designator

### ORDERING INFORMATION

| Device      | Package             | Shipping      |
|-------------|---------------------|---------------|
| MBR2535CTLG | TO-220<br>(Pb-Free) | 50 Units/Rail |

# MBR2535CTLG

## MAXIMUM RATINGS (Per Leg)

| Rating                                                                                                                 | Symbol                          | Value       | Unit             |
|------------------------------------------------------------------------------------------------------------------------|---------------------------------|-------------|------------------|
| Peak Repetitive Reverse Voltage<br>Working Peak Reverse Voltage<br>DC Blocking Voltage                                 | $V_{RRM}$<br>$V_{RWM}$<br>$V_R$ | 35          | V                |
| Average Rectified Forward Current<br>( $T_C = 142^\circ\text{C}$ per Diode)<br>( $T_C = 142^\circ\text{C}$ per Device) | $I_{F(AV)}$                     | 12.5<br>25  | A                |
| Peak Repetitive Forward Current, per Leg (Sq Wave, 20 kHz, $T_C = 139^\circ\text{C}$ )                                 | $I_{FRM}$                       | 25          | A                |
| Non-Repetitive Peak Surge Current<br>(Surge Applied at Rated Load Conditions, Halfwave, Single Phase, 60 Hz)           | $I_{FSM}$                       | 150         | A                |
| Peak Repetitive Reverse Surge Current (2.0 $\mu\text{s}$ , 1.0 kHz)                                                    | $I_{RRM}$                       | 1.0         | A                |
| Storage Temperature Range                                                                                              | $T_{stg}$                       | -65 to +150 | $^\circ\text{C}$ |
| Operating Junction Temperature (Note 1)                                                                                | $T_J$                           | -65 to +150 | $^\circ\text{C}$ |
| Voltage Rate of Change (Rated $V_R$ )                                                                                  | $dv/dt$                         | 10,000      | V/ $\mu\text{s}$ |
| Controlled Avalanche Energy                                                                                            | $W_{aval}$                      | 20          | mJ               |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. The heat generated must be less than the thermal conductivity from Junction-to-Ambient:  $dP_D/dT_J < 1/R_{\theta JA}$ .

## THERMAL CHARACTERISTICS

| Characteristic                                  | Conditions | Symbol          | Max  | Unit                      |
|-------------------------------------------------|------------|-----------------|------|---------------------------|
| Maximum Thermal Resistance, Junction-to-Case    | Min. Pad   | $R_{\theta JC}$ | 2.0  | $^\circ\text{C}/\text{W}$ |
| Maximum Thermal Resistance, Junction-to-Ambient | Min. Pad   | $R_{\theta JA}$ | 75.0 |                           |

## ELECTRICAL CHARACTERISTICS

| Characteristic                                                                                                                                                                                                | Symbol | Min         | Typical              | Max                  | Unit |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|-------------|----------------------|----------------------|------|
| Instantaneous Forward Voltage (Note 2)<br>( $i_F = 25\text{ A}$ , $T_J = 25^\circ\text{C}$ )<br>( $i_F = 12.5\text{ A}$ , $T_J = 25^\circ\text{C}$ )<br>( $i_F = 12.5\text{ A}$ , $T_J = 125^\circ\text{C}$ ) | $V_F$  | –<br>–<br>– | 0.51<br>0.41<br>0.33 | 0.55<br>0.47<br>0.41 | V    |
| Instantaneous Reverse Current (Note 2)<br>(Rated dc Voltage, $T_J = 25^\circ\text{C}$ )<br>(Rated dc Voltage, $T_J = 125^\circ\text{C}$ )                                                                     | $i_R$  | –<br>–      | 0.8<br>300           | 5.0<br>500           | mA   |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2. Pulse Test: Pulse Width = 300  $\mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .

# MBR2535CTLG




Figure 1. Typical Forward Voltage




Figure 2. Maximum Forward Voltage




Figure 3. Typical Reverse Current, Per Leg




Figure 4. Current Derating, Case, Per Leg




Figure 5. Current Derating, Ambient, Per Leg




Figure 6. Forward Power Dissipation

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)